

SP PRO SERIES

The Selectronic SP PRO SERIES has been designed from the ground up with the world market in mind. Using our 25 years of experience in the harsh Australian market, we have developed a product which will suit many different markets including; Off Grid, On Grid with back up, Marine, Mobile and Industrial. Featuring advanced thermal power management and super high speed digital signal processing, new standards have been set for reliability, features, surge capability and power density.

The SP PRO series will act as a low voltage grid feeding inverter and will provide back-up power to the load if grid electricity has failed. The unit can also be configured to operate as an Interactive Inverter Charger, with fast preset configurations for either mobile or remote power system use.



Features

- » Ratings @ 40°C
- » Low distortion sine wave Interactive Inverter Charger with grid feed ability
- » Advanced thermal techniques provide excellent high temperature performance
- » 63 amp AC transfer switch with anti-chatter protection
- » Grid feeds with excess renewable
- » "Grid Lockout" setting can allow battery charging "Off Peak"
- » Automatic changeover when grid fails without using a second inverter
- » World leading 300% surge capacity
- » True 100% charge capacity
- » Five stage battery charging with dual float points and adjustable temperature compensation
- » Battery mid point monitoring with automatic equalisation
- » Simple LED display, with the AC LEDs directly powered from the monitored voltage
- » Redundant safety disconnect for pluggable operation
- » Plug and play or fully configurable via computer
- » Eighteen months of logged daily totals
- » Four months of sampled data at 30 minute sample rate
- » Adjustable 30/15/10/5/1 minute sample rate
- » Easy to use configuration/ monitoring software supplied standard
- » "Partial state of charge" control can minimise generator run time
- » Superbly quiet
- » All PCBs conformal coated with mil spec silicone
- » 4 x addressable relay outputs and 3 x digital outputs
- » 4 x addressable digital inputs and 2 x analogue inputs
- » 2 x user definable shunt inputs
- » Low battery shutdown override in case of emergency
- » Discretionary load control
- » External solar regulator bypass function
- » 2 x serial ports with power for accessories
- » Variable speed fan with service alert
- » Lifetime monitored capacitors with service alert
- » Warranty, 5 yrs + 2 for SP PRO accredited installers
- » 100% Australian designed and manufactured
- » Field serviceable modular design*

*Conditions Apply

SP PRO SERIES SPECIFICATIONS		SPMC 241-AU	SPMC 481-AU	SPMC 482-AU
Nominal battery voltage		24 V	48 V	48 V
Continuous, output power	@ 40°C	3500 W	4000 W	6000 W
Continuous, charge current		145 A	83 A	125 A
Continuous, output power	@ 25°C	4000 W	4500 W	7000 W
Continuous, charge current		146 A	83 A	125 A
20 second load rating	@ 40°C	10500 W	12000 W	18000 W
20 second output current		40 A	47 A	70 A
1 minute output power	@ 40°C	7600 W	8700 W	13000 W
60 minute output power	@ 40°C	4700 W	5300 W	8000 W
DC input voltage range		20 - 34 V	40 - 68 V	40 - 68 V
TRANSFER SWITCH				
AC transfer current capacity		63 A		
Max AC input source, (generator) W		15 kW		
Max total output to Load, AC source + inverter		15 kW		
AC transfer time		no-break		
If grid fails		two AC cycles		
Battery charger type		5 stage, power factor corrected with dual stage float		
DC consumption idle		6 W		
Standby (adjustable rate)		12 - 20 W		
ON with no load		36 W	37 W	40 W
Peak efficiency – all modes		95%	95.5%	96%
10% load		90.5%	91%	91%
20% load		93%	94%	94%
50% load		94.5%	95%	95.5%
100% load		91%	92.5%	93%
Max Grid Feed capacity		rated output		
AC OUTPUT standalone				
Setting accuracy		210 to 240 V+/- 1%		
Regulation		<2% droop @ 0-200% rated load (<5% 0-300%)		
THD		<3% @ 0-200% rated load		
Frequency		50 or 60 Hz +/-0.005% standalone		
AC SOURCE (input)				
Nominal voltage		210 to 240 V~		
Tolerance on nominal voltage		programmable - 1% to 15%, + 1% to 10%		
Nominal input frequency		50/60Hz		
Tolerance on nominal frequency		programmable +/- 1% to 10%		
Generator can be started by		battery SoC, DC voltage, battery load, unit temperature, time & remote control		
Battery temperature sensor		Yes		
Mid point battery voltage sensing		Yes		
Inverter display		22 x LEDs with auto adjusting intensity. Display indicates, charger status, remaining useable battery capacity, alarms, AC status. AC status LEDs powered from AC voltage. Generator control button. Output mode button. Alarm silence button.		
Digital Inputs		4 off		
Shunt Inputs		2 user definable: +/-75mV		
Analogue Inputs		2 general purpose logged 0-60V		
Relay Outputs		4 off: 60 V, 500 mA		
Digital outputs		3 off: 60 V, 5 mA		
Communication ports		2 off RS232 with adjustable baud rate of up to 57600		
Memory retention of settings & data		permanent		
SP LINK configuration and monitoring software		Standard, allows configuration of parameters or customer can view LED & digital display remotely.		
Dimensions (mounted)		345 W x 545 H x 215 D		
Weight		34 kg	35 kg	40 kg
Circuit Breakers		double pole 63A for both AC Source and AC Load		
Standards		EN61000-6-3 2007, AS3100 2002, AS4777 2005 (grid connect)		
Protection		IP43		
Warranty		7 years when installed by a Selectronic SP PRO accredited installer (conditions apply)		
Availability		AUS: Feb 09 NZ: April 09	AUS: Feb 09 NZ: April 09	AUS: Now NZ: March 09
Grid Approval		May 2009	May 2009	May 2009
Introductory Price (retail incl GST)		\$6,690	\$7,790	\$8,990

Through a policy of continual improvement specifications may differ from this brochure.
All ratings are at @ 25°C and nominal battery voltage unless otherwise stated and correct as at Feb 09.

+61 3 9727 6600
sales@selectronic.com.au
www.selectronic.com.au



POWER PERFORMANCE PASSION